

ProxPoint Plus

125 khz Value Priced Proximity Reader



- Small sized, low cost reader features a beeper and multi color LED which can be host and/or locally controlled
- Potted reader suitable for indoor or outdoor use
- Power requirements: 5-16 VDC
- Current requirements: 20mA avg / 75mA peak at 12VDC
- Dimensions: 3.135" x 1.70" x 0.66" (7.96 x 4.3 x 1.68 cm)
- Base part numbers: 6005 (Wiegand), 6008 (Clock-and-Data)

MaxiProx

125 khz Long Range Proximity Card Reader



- Long read range distance (up to 8' with ProxPass ®)
- Autotune allows read range to be maintained within four inches of metal
- Wiegand, Clock-and-Data, RS-232, RS-422, and RS-485 output modes are configurable
- "Parking hold" feature ensures accurate detection of vehicles in parking lanes
- Power requirements: 12 or 24 VDC (configurable)
- Current requirements: 200mA avg / 700 mA peak at 12VDC; 260mA avg / 1.2A peak at 24 VDC



* Due to continuous product enhancement, Sin Chew Alarm reserves the right to change / modify specification without prior notice.

No.10 Upper Aljunied Link #06-02/03/04 Johnson C. Building Singapore 367904

24 Hr Service Tel: (65) 6287 2788 Fax: (65) 6287 0856

Email: enquiry@sinchewalarm.com <http://www.sinchewalarm.com>



Cert No: 054650